


SuperServer 6029U-TR4 (Complete System Only)



Integrated Board



Super X11DPU

**Views: | [Angled View](#) | [Top View](#) |
| [Front View](#) | [Rear View](#) |**

Complete System Only: To maintain quality and integrity, this product is sold only as a completely-assembled system (with minimum 2 CPUs and 4 DIMMs).

[▶ Drivers & Utilities](#)
[▶ BIOS](#)
[▶ IPMI](#)
[▶ Tested Memory](#)
[▶ Tested M.2 List](#)
[▶ NVMe Options](#)
[▶ Manuals](#)
[▶ OS Certification Matrix](#)
[▶ Compatible GPU List](#)
[▶ Quick-References Guide](#)
[▶ Drive Options](#)
[▶ Network Card \(AOC\) Matrix](#)

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.



Key Features

- Virtualization
- Hyperconverge Storage
- Cloud Computing
- High End Enterprise Server
- Flexible Networking Options

1. Dual Socket P (LGA 3647) support 2nd Gen Intel® Xeon® Scalable processors (Cascade Lake/Skylake)‡
2. 24 DIMMs; up to 6TB 3DS ECC DDR4-2933MHz† RDIMM/LRDIMM, Supports Intel® Optane™ DCPMM††
3. 1 PCI-E 3.0 x16 slot (FH, 10.5" L), 5 PCI-E 3.0 x8 slots (FH, 10.5" L), 1 PCI-E 3.0 x8 slot (LP), 1 PCI-E 3.0 x8 slot (internal LP)
4. 4 1GbE LAN ports via Intel i350AM4
5. 12 Hot-swap 3.5" drive bays: 12 SATA (opt. 8 SAS3 + 4 NVMe/SAS3), Optional 2 hot-swap 2.5" rear drive bays for SSDs; Optional M.2 NVMe and SATA3 ports
6. 4 Heavy duty 8cm fans
7. 1000W High efficiency (96%) Redundant PSU; **Titanium Level**

Specifications

Product SKUs

SYS-6029U-TR4 ■ SuperServer 6029U-TR4 (Black)

Motherboard

Super X11DPU

Processor/Cache

CPU ■ Dual Socket P (LGA 3647)
 ■ 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors[‡],
 Dual UPI up to 10.4GT/s
 ■ Support CPU TDP 70-205W

Cores ■ Up to 28 Cores

Note [‡] BIOS version 3.2 or above is required to support 2nd Gen Intel® Xeon® Scalable processors (codenamed Cascade Lake-R)

System Memory

Memory Capacity ■ 24 DIMM slots
 ■ Up to 6TB 3DS ECC DDR4-2933MHz[†] RDIMM/LRDIMM
 ■ Supports Intel® Optane™ DCPMM^{††}

Memory Type ■ 2933[†]/2666/2400/2133MHz ECC DDR4 RDIMM/LRDIMM
 ■ 2666 ECC DDR4 NVDIMM

Note [†] 2933MHz in two DIMMs per channel can be achieved by using memory purchased from Supermicro
^{††} Cascade Lake only. Contact your Supermicro sales rep for more info.

On-Board Devices

Chipset ■ Intel® C621 chipset

SATA ■ SATA3 (6Gbps) with RAID 0, 1, 5, 10

Network Connectivity ■ 4 GbE ports via AOC-2UR68-I4G-P (Intel i350AM4)

IPMI ■ Support for Intelligent Platform Management Interface v.2.0
 ■ IPMI 2.0 with virtual media over LAN and KVM-over-LAN support

Graphics ■ ASPEED AST2500 BMC

Input / Output

SATA ■ 12 SATA3 (6Gbps) ports

SAS ■ 8 SAS3 + 4 SAS3/NVMe support optional

LAN ■ 4 RJ45 Gigabit Ethernet LAN ports
 ■ 1 RJ45 Dedicated IPMI LAN port

USB ■ 3 USB 3.0 ports (2 rear, 1 Type A)

Video ■ 2 VGA ports (1 rear, 1 onboard)

Serial Port / Header ■ 1 Serial header

DOM ■ 2 SuperDOM (Disk on Module) ports

Chassis

Form Factor ■ 2U Rackmount

Model ■ CSE-829U2TS-R1K02P-T

Dimensions and Weight

Width ■ 17.2" (437mm)

Height ■ 3.5" (89mm)

Depth ■ 28.46" (723mm)

Weight ■ Net Weight: 36 lbs (16.4 kg)
 ■ Gross Weight: 72 lbs (32.7 kg)

Available Colors ■ Black

Front Panel

Buttons ■ Power On/Off button
 ■ System Reset button

LEDs ■ Power status LED
 ■ HDD activity LED
 ■ Network activity LEDs
 ■ System information (overheat/UID) LED

Expansion Slots

PCI-Express ■ 1 PCI-E 3.0 x16 (FH, 10.5" L)
 ■ 5 PCI-E 3.0 x8 (FH, 10.5" L)
 ■ 1 PCI-E 3.0 x8 (LP)
 ■ 1 PCI-E 3.0 x8 (internal LP)

(Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram and AOC Support for details.)

Drive Bays / Storage

Hot-swap ■ 12 Hot-swap 3.5" drive bays
 ■ 12 SATA3 ports by default;
 Optional 8 SAS3 + 4 NVMe/SAS3

M.2 ■ 1 M.2 PCI-E 3.0 x4 M-Key NVMe or 1 M.2 M-Key SATA3 (2240/2260/2280/22110) via optional riser card (see optional parts list)
 ■ 2 M.2 PCI-E 3.0 x4 M-Key NVMe (2260/2280/22110) via optional add-on card AOC-SLG3-2M2

Backplane

2U SAS/SATA backplane

System Cooling

Fans ■ 4 Heavy duty 8cm PWM fans

Power Supply

1000W Redundant Power Supplies with PMBus

Total Output Power ■ 800W: 100 – 127Vac
 ■ 1000W: 200 – 240Vac
 ■ 1000W: 200 – 240Vdc (for CCC only)

Dimension (W x H x L) ■ 73.5 x 40 x 203 mm

System BIOS

- | | |
|------------------|--|
| BIOS Type | <ul style="list-style-type: none"> AMI 32Mb SPI Flash ROM |
|------------------|--|

Management

- | | |
|-----------------|--|
| Software | <ul style="list-style-type: none"> Intel® Node Manager <u>IPMI 2.0</u> KVM with dedicated LAN NMI <u>SSM, SPM, SUM</u> <u>SuperDoctor® 5</u> |
|-----------------|--|

- | | |
|-----------------------------|---|
| Power Configurations | <ul style="list-style-type: none"> ACPI Power Management |
|-----------------------------|---|

PC Health Monitoring

- | | |
|------------|--|
| CPU | <ul style="list-style-type: none"> Monitors for CPU Cores, Chipset Voltages, Memory. 4+1 Phase-switching voltage regulator |
|------------|--|

- | | |
|------------|---|
| FAN | <ul style="list-style-type: none"> Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors |
|------------|---|

- | | |
|--------------------|--|
| Temperature | <ul style="list-style-type: none"> Monitoring for CPU and chassis environment Thermal Control for fan connectors |
|--------------------|--|

- | | |
|--------------|--|
| Input | <ul style="list-style-type: none"> 100-127Vac / 9.8 - 7A / 50-60Hz 200-240Vac / 7 - 5A / 50-60Hz 200-240Vdc / 7 - 5A (for CCC only) |
|--------------|--|

- | | |
|-------------|---|
| +12V | <ul style="list-style-type: none"> Max: 66.7A / Min: 0A (100-127Vac) Max: 83A / Min: 0A (200-240Vac) Max: 83A / Min: 0A (200-240Vdc) |
|-------------|---|

- | | |
|--------------|---|
| 12Vsb | <ul style="list-style-type: none"> Max: 2.1A / Min: 0A |
|--------------|---|

- | | |
|--------------------|--|
| Output Type | <ul style="list-style-type: none"> 25 Pairs Gold Finger Connector |
|--------------------|--|

Certification

Titanium Level
[**Test Report**]

Operating Environment

- | | |
|-------------|--|
| RoHS | <ul style="list-style-type: none"> RoHS Compliant |
|-------------|--|

- | | |
|----------------------------|---|
| Environmental Spec. | <ul style="list-style-type: none"> Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing) |
|----------------------------|---|

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11DPU	1	Super X11DPU Motherboard
	CSE-829U2TS-R1K02P-T	1	2U Chassis
Add-on Card / Module	AOC-2UR68-I4G-P	1	2U Ultra Riser based on Intel i350AM4 controller with 4 GbE RJ45 ports, 1 internal PCI-E x8 3.0 slot, 1 PCI-E x16 3.0, and 1 PCI-E x8 3.0 (in x16 slot)
Backplane	BPN-SAS3-826A-N4	1	12-port 2U SAS3 12Gbps hybrid backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD and 4x SAS3/SATA3/NVMe Storage Devices
Cable 1	CBL-PWEX-0652	1	8 pin female to 2x RA(Right Angle) big 4 pin female power, 60/65CM, 18AWG,RoHS/REACH
Cable 2	CBL-PWEX-0673	1	8 pin female to 2x big 4 pin female power, 65/70CM, 18AWG,RoHS/REACH
Cable 3	CBL-SAST-0655	1	MINI SAS HD(ST)-MINI SAS(RA-RS EXIT),6G,INT,47CM,SB,30AWG
Cable 4	CBL-SAST-0656	1	MINI SAS HD(ST)-MINI SAS(RA-RS EXIT),6G,INT,39CM,SB,30AWG
Cable 5	CBL-SAST-0657	1	MINI SAS HD(ST)-MINI SAS(RA-RS EXIT),6G,INT,55CM,SB,30AWG
Air Shroud	MCP-310-82921-0N	1	Plastic air shroud for SC829U, 219U (X11 24DIMM, left side)
Air Shroud	MCP-310-82922-0N	1	Plastic air shroud for SC829U, 219U (X11 24DIMM, right side)
Riser Card	RSC-R1UW-E8R	1	1U RHS WIO Riser card with one PCI-E x8 slot
Riser Card	RSC-R2UW-4E8	1	2U LHS WIO Riser card with four PCI-E x8 slots
Heatsink / Retention	SNK-P0068PS	2	2U Passive CPU Heat Sink for X11 Purley Platform Equipped with a Narrow Retention Mechanism
Power Supply	PWS-1K02A-1R	2	1U 1000W Redundant Power Supply 73.5mm width Titanium Level,RoHS/REACH
FAN 1	FAN-0118L4	4	80 x 80 x 38 mm, 9.5K RPM, 4-pin PWM Fan, Hot

Optional Parts List

	Part Number	Qty	Description
Add-on card for internal M.2 NVMe	AOC-SLG3-2M2	1	Low Profile PCI-E x8 add-on card supports 2 PCI-E 3.0 x4 M-Key M.2 NVMe Modules
2U Cable Management Arm	MCP-290-00128-0N & MCP-290-00127-0N	1	2U Supermicro Cable Management Arm 2nd Gen (Compatible for racks that are 42" in depth)
Internal Drive Tray for Two 2.5" Drives	MCP-120-82916-0N	1	Internal drive plate Supports Two 2.5" Drive, PCI slots
	CBL-PWEX-0650	1	Power cable for Two internal 2.5" drives
	CBL-0080L	2	
	CBL-0484L Or CBL-SAST-0654 Or	2	SATA3 S-S Cable
	CBL-SAST-0948	1	miniSAS(iPass) to 4 SATA Cable
Cable for 4 NVMe Hybrid Drive Bays	2 CBL-SAST-0929 & 2 CBL-SAST-0972	1	OCuLink source to MiniSAS HD target V.91,INT,PCIe NVMe SSD, 57CM,34AWG
Hot-swap 3.5" to 2.5" NVMe Drive Tray	MCP-220-00138-0B	1~4	Tool-less black hot-swap 3.5-to-2.5 converter NVMe drive tray (Orange tab)
Hot-swap 3.5" to 2.5" SATA/SAS Drive Trays	MCP-220-00118-0B	1~12	Tool-less black hot-swap 3.5-to-2.5 converter HDD drive tray (Red tab)
	MCP-220-00043-0N		Black hot-swap 3.5-to-2.5 converter HDD drive tray (Red tab)
2 Internal M.2 slots (1 SATA, 1 NVMe)	RSC-UMR-8 & CBL-SAST-0538 & MCP-120-82924-0N & MCP-310-21902-0N	1	1U Ultra RHS Riser Card with 1 PCIE/SATA Hybrid M.2 & 1 PCIE X8

2 Rear 2.5" Hot-swap SATA Drive Bays (Complete System Only)	MCP-240-82922-0N-OEM	-	Rear 2x 2.5" HDDs riser bracket kit for SC829U/219U, tool-less
Storage Control Card and Cable(s)	AOC-S3008L-L8e & 2x CBL-SAST-0593	1~2	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 122HDD, HBA; MINI SAS HD,12G,INT,60CM,30AWG
	AOC-S3008L-L8i & 2x CBL-SAST-0593		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 63HDD, RAID 0,1,1E; MINI SAS HD,12G,INT,60CM,30AWG
	AOC-S3108L-H8iR & 2x CBL-SAST-0593		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60; MINI SAS HD,12G,INT,60CM,30AWG
	AOC-S3108L-H8iR-16DD & 2x CBL-SAST-0593		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 16HDD, RAID 0, 1, 5, 6, 10, 50, 60; MINI SAS HD,12G,INT,60CM,30AWG
Network Card(s)	AOC-SGP-i2/4	-	Standard LP, 2/4x GbE RJ45, PCI-E x4, Intel i350
	AOC-STGN-i1S/i2S	-	Standard LP, 1/2x 10GbE SFP+, PCI-E x8, Intel 82599EN
	AOC-STGF-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel XL710-BM2
	AOC-STG-i4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Intel XL710
	AOC-STG-b4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S
	AOC-STG-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel X540
	AOC-STGS-i1/2T	-	Standard LP, 1/2x 10GbE RJ45, PCI-E x8, Intel X550
	AOC-STG-i4T	-	Standard LP, 4x 10GbE RJ45, PCI-E x8, Intel XL710
	AOC-STG-i2	-	Standard LP, 2x 10GbE CX4, PCI-E x8, Intel 82598EB
	AOC-S25G-m2S	-	Standard LP, 2x 25GbE SFP28, Mellanox ConnectX-4 LX EN
	AOC-S40G-i2Q	-	Standard LP 2-port 40GbE controller, Intel Fortville XL710
	More	-	AOC Compatibility Matrix
CacheVault(s)	BTR-CV3108-U1	-	CacheVault for Broadcom 3108 with Supercap mounting for 2U Ultra
Hot-swap 3.5" to 2.5" Hard Disk Drive Tray	MCP-220-00043-0N	-	Black hot-swap 3.5" to 2.5" HDD tray
TPM security module	AOM-TPM-9670H-S	1	TCG 2.0 compliant trusted platform module (TPM), Horizontal FF
	AOM-TPM-9671H-S	1	TCG 1.2 compliant trusted platform module (TPM), Horizontal FF
Intel VROC RAID Key	AOC-VROCINTMOD	1	Intel VROC, RAID 0, 1, 5, 10 (Intel SSD Only)
	AOC-VROCSTNMOD	1	Intel VROC Standard, RAID 0, 1, 10
	AOC-VROCPREMOD	1	Intel VROC Premium, RAID 0, 1, 5, 10
Global Services & Support	OS4HR3/2/1	-	3/2/1-year onsite 24x7x4 service
	OSNBD3/2/1	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC • eStore	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)